



TUMOSAN

5200S SERIES

5255S | 5265S

8 + 8



Friend of Your GARDEN



Powerful Engine



High Traction Performance
Low Fuel Consumption

 5255S 55HP

 5265S 65HP

DOMESTIC ENGINE
DOMESTIC ENGINEERING



Fuel tank with a capacity of **65 liters** that provides uninterrupted operation throughout the day.



Battery Circuit Breaker

Long-lasting accumulator use with the **Mechanical Accumulator Circuit Breaker** positioned inside the front body.



PTO Shaft Control Button

PTO Control Button designed for safe PTO shaft use.

*When the operator leaves the seat while the PTO is in operation, the sensor located under the seat gives a warning within 7 seconds and disables the PTO.



Hood Lock

Safer use with the **Hood Lock**, which is offered as standard in all our models.



Rops System

Rops System with additional piston integration for comfortable lowering and lifting.



Dashboard

Superior driving control with **Digital Instrument Panel and Audible Warning System.**



Control Levers

Effective use with ergonomic **Hydraulic Control Levers** positioned on the right side of the operator.



PTO Shaft

PTO Control Lever and PTO Speed Lever with 540/540E rpm double speed option positioned on the left side of the operator.



Control Panel

Ease of use with **Electro-Hydraulic** controlled **Two-wheel Drive, Front and Rear Differential Lock System** offered as standard.

*If the operator applies the brakes, it automatically switches to two-wheel drive.



Transmission

Unique use with **8 Forward-8 Reverse** gear options that allow the operator to catch the appropriate speed.

*In all models, the **forward-backward raceway** is positioned under the steering wheel.



Valve System

Thanks to the **4 Hydraulic Power Outputs** offered as standard, it is possible to work uninterruptedly with the equipment that needs hydraulics.

Lifting Capacity

Hydraulic system with a lifting capacity of **2200 kg** in all models.



Tow System

Height-adjustable, durable **Elevator Tow System** that provides ease of use to the operator.

5200S Series Technical Specifications

MODELS	5255S	5265S
ENGINE		
Emission Level	Stage IIIA	
Rated Motor Power (HP)	55	65
Number of Cylinders / Aspiration	3 / Turbo Intercooler	
Cylinder Volume (liter)	2,9	
Maximum Torque (Nm)	220	260
Maximum Torque Speed (rpm)	1500	
Air Filter Type	Dry	
Fuel Tank Capacity (liter)	65	
Battery Circuit Breaker	Standard	
TRANSMISSION		
Gearbox Type	Mechanical - Synchromesh	
Gear Option	8 Forward - 8 Backward	
Forward - Reverse Raceway	Mechanical (Under Steering Wheel)	
Two-Wheel Control - 4WD	Electro - Hydraulic	
Front Differential Lock - 4WD	Electro - Hydraulic	
Rear Differential Lock	Electro - Hydraulic	
PTO SHAFT		
Type	Independent	
Control Type	Mechanical	
PTO Speed Synchronized to Wheel Speed	Standard	
PTO Speed (rpm)	540-540E	
Engine Speed @540 rpm PTO Speed	2035	
Engine Speed @540E rpm PTO Speed	1586	
HYDRAULIC SYSTEM		
Control Type	Mechanical	
Lift Automatic	Standard	
Hydraulic Power Output	4	
Lifting Capacity (kg)	2200	
Tow System	Elevator Tow	
WEIGHTS		
Total Front Bag Weight (pcs x kg)	6 x 20	
Total Counterweight - 24" Wheel (pcs x kg)	4 x 35	
Total Counterweight - 28" Wheel (pcs x kg)	4 x 50	
Unladen Mass (kg)	2450	
TIRE OPTIONS (4WD)		
Front	280/70R16	
Rear	380/70R24	
Front	280/70R20	
Rear	380/70R28	

