



AVENGER 26 HST 4WD

ENGINE		
Model / Make	MVS3L2 / MHI	
HP Category	26	
Туре	4 cycle, vertical overhead valve, cylinder in line, swirl chamber type	
No. of Cylinders	3 Cylinder Vertical Inline	
Bore / Stroke (mm)	78 / 92	
Rated Engine (RPM)	2500	
Displacement (cc)	1319	
Fuel Pump	In-Line type (ND-PFR M Type)	
Air Cleaner Type	Dry with Clogging Sensor	
Cooling System	Water Cooled	
CLUTCH		
Drive	Selected 4WD	
TRANSMISSION		
Туре	HYDROSTATIC TRANSMISSION	
ROAD SPEED KM/hr	FORWARD	REVERSE
Low	3.02	3.02
Medium	9.6	9.6
High	19.01	19.01
MID-MOUNT MOWE	R SPECIFICATION	
Mounting Method	Ground Following	
Cutting Width in. (mm)	54 (1371.6)	
Cutting Height in. (mm)	1-4 (25.4-101.6)	
Number of Blades	3	
STEERING	141	
Туре	Power Steering	
HYDRAULIC SYSTEM	И	
Туре	Open Center, ADDC	
Hydraulic Pump	Gear Type	
Lifting Linkage	TPL Category 1N	
Lifting Capacity (kg)	750	

Technical Specifications

POWER TAKE OFF		
Туре	Hydraulic Clutch	
Rear PTO	6 Splines	
Speed / Engine RPM	540 @ 2500	
Mid PTO	15 Spline	
Speed / Engine RPM	1781 @ 2500	
CAPACITIES (LITRES)		
Fuel Tank	25	
Engine Sump	4.2	
Cooling System	4.8	
Transmission Oil	14±10%	
ELECTRICAL INSTALL	ATION	
Battery	12V, 65Ah	
Alternator	12V, 40A	
Starter Motor	12V, 1.6 KW	
MIN. TURNING RADIU	s	
Without Brakes (m)	2.5	
TYRE SIZE	TURF	AGRI
Front	18 x 8.50 -10 Pr4	6.00 - 12
Rear	26 x 12.00 - 12 Pr4	8.3 - 20
FRONT DRIVE AXLE fo	or 4WD Only	
Differential		
Total Ratio	1:13.81	
Oil Capacity (Ltr.) Total	3.2 Ltr.	
BRAKES		
Туре	Wet Disc	
DIMENSIONS		
Overall Length	2860 mm	
Width	1065 mm	
Height	2290 mm	
Ground Clearance	320 mm	
Wheel Base	1535 mm	
Front Track	860 mm (Std.)	
Rear Track	820 mm (Std.)	

For further details please contact nearest dealer

AVENGER TRACTORS

Patiala Road, Nabha-147 201 (Pb.) INDIA

E-mail: info@avenger.co.in | Website: www.avenger.co.in