



EUROPEAN SERIES

Definitely Built for
Hardcore Performance

AVENGER 40 XM 2WD



More Power in Less Fuel Consumption
Low Maintenance Cost

Available Tractor Range
20 HP to 100 HP



AVENGER 40 XM 2WD

Technical Specifications

ENGINE		
Model / Make	AVENGER 40 XM	
HP Category	40	
Type	Four Stroke DI, Liquid Cooled	
No. of Cylinders	3 Cylinder, Vertical Inline	
Bore / Stroke (mm)	102 / 118	
Rated Engine (RPM)	2200	
Displacement (cc)	2892	
Fuel Pump	Multicylinder Inline (BOSCH)	
Air Cleaner Type	Dry	
Cooling System	Water Cooled	
TRANSMISSION		
Gear Box	8F + 2R Combination of Constant & Sliding Mesh, Side Shift	
Clutch	Heavy Duty Dry Dual 280 mm (Single Optional) Cerametallic Plates	
Brakes	Oil Immersed Brakes	
Road Speed Km/hr		
Gear	LOW	HIGH
1	2.51	9.90
2	3.09	13.03
3	5.13	20.20
4	8.10	31.90
Reverse	3.52	13.86
MIN. TURNING RADIUS		
Without Brakes (m)	3.9	
STEERING		
Type	Power Steering	

E-mail : info@avenger.co.in
 Website : www.avenger.co.in

HYDRAULIC SYSTEM	
Type	2 Lever, ADDC
Hydraulic Pump	Gear Type
Linkage	TPL Category-II
Lifting Capacity (Kg.)	1800
POWER TAKE OFF	
Splines	6
P.T.O. Speed	540 with GPTO
CAPACITIES (LITRES)	
Fuel Tank	67
Engine Sump	7
Cooling System	8.5
Transmission & Hydraulic	55
Steering System	2 (PS)
TYRE SIZE	
Front	6.00 - 16
Rear	13.6 - 28 (14.9 - 28 Optional)
Weight (Kg.)	2010
DIMENSIONS	
Overall Length	3750 mm
Width	1780 mm
Height upto Exhaust	2220 mm
Ground Clearance	395 mm

For further details please contact nearest dealer

Note: Being subject to design changes & improvement in our company policy, all products, and product specifications are subject to change without prior notice to improve reliability, features or design or otherwise.