



EUROPEAN SERIES

Definitely Built for
Hardcore Performance

AVENGER 60 XT 2WD



More Power in Less Fuel Consumption
Low Maintenance Cost

Available Tractor Range
20 HP to 100 HP*



AVENGER 60 XT 2WD

Technical Specifications

ENGINE				
Model / Make	AVENGER 60 XT			
HP Category	60			
Type	Four Stroke DI			
No. of Cylinders	4 Cylinder, Vertical, Inline			
Bore / Stroke (mm)	105 / 118			
Rated Engine (RPM)	2200			
Displacement (cc)	4085			
Fuel Pump	Multicylinder Inline (BOSCH)			
Air Cleaner Type	Dry			
Cooling System	Water Cooled			
CLUTCH				
Type	Heavy Duty, Dry Type Double clutch			
Plate Size	(310 / 340) Cerametallic Friction			
TRANSMISSION				
Gear Box	8F + 2R, Combination of Sliding & Constant Mesh / 12+12			
ROAD SPEED KM/hr	FORWARD	REVERSE		
Gear	HIGH	LOW	HIGH	LOW
1	11.21	2.84	15.77	3.99
2	13.82	3.53		
3	22.89	5.82		
4	36.25	9.20		
HYDRAULIC SYSTEM				
Type	2 Lever, ADDC			
Hydraulic Pump	Gear Type			
Linkage	TPL Category I-II			
Lifting Capacity (kg)	1800 / 2200			
STEERING				
Type	Power Steering			

Note: As per our policy of continuous development, specifications may change without any prior notice. For further details contact your nearest dealer.

E-mail : info@avenger.co.in
 Website : www.avenger.co.in

POWER TAKE OFF	
Type	Dual Speed Live
Splines	6
PTO / Speed	540 and CR PTO
CAPACITIES (LITRES)	
Fuel Tank	67
Engine Sump	11
Cooling System	9.5
Transmission & Hydraulic	55 / 35 (12+12)
Steering System	2
ELECTRICAL INSTALLATION	
Battery	12V, 100Ah
Alternator	12V, 42A
Starter Motor	12V, 2.7 KW
MIN. TURNING RADIUS	
Without Brakes (m)	5.24
TYRE SIZE	
Front	7.50 - 16
Rear	16.9 x 28
Weight (Kg.)	2190 (W/O ROPS)
BRAKES	
Type	Multi Disc Oil Immersed
DIMENSIONS	
Overall Length	3875 mm
Width	1930 mm
Height upto Exhaust	2280 mm
Ground Clearance	415 mm
Wheel Base	2230 mm
Front / Rear Track	1425 mm / 1480 mm

Authorised Dealer :

