

HT08

MINI EXCAVATOR

Quick and easy replacement of accessories

Multi-functions

Long Life

Strong Power

360° Rotate

Low Consumption

PARAMETER

MODEL : HT08

Performance Parameter		Working Range	
Rated power	12HP	Max.digging distance	2450mm
Bucket Capacity	0.025 m³	Max.digging depth	1300mm
Bucket width	300mm	Max.digging height	2350mm
Engine Model	Changchai 192	Max.dumping height	1600mm
Optional Engine	Koop Europe 5	Min.Swing radius	1100mm
	BRIGGS & STRATTON	Max. Upgrade height of bulldozer blade	120mm
Operating Weight	800 kg	Max. Digging depth of bulldozer blade	200mm
Max. digging force	7.5KN	Dimensions	
Pump form	Single gear pump	Total width	720-780mm
Set working pressure	14Mpa	Total height	1300mm
Swing speed	12 rpm	Total length	2430mm
Travel speed	2.2Km/h	Min. ground clearance	80mm
Gradeability	30°	Track ground length	1140mm
Ground pressure	19Kpa	Track width	150mm

Quick and easy replacement of accessories

ACCESSORIES

Multi-functions

Auger

Bucket

Grabber

Narrow Bucket

Rake

Ripper

Break Hammer

Plain Bucket

Quick Hitch

Trailer

FIRST-CLASS CONFIGURATION

EXCAVATOR FACTORY

01

Unique big arm structure design not easy to break

Other factory arm easy broken design

Our

Other

02

The operation front pipeline is clear

The protective cover protects the pipeline from being destroyed

03

The boom cylinder adopts the well-known brand

The cylinder is designed integrated, which is more advanced than the welding technology.

04

All structural parts are finely processed

Shot blasting, pickling, and baking finish process are adopted. The surface has high gloss and high paint adhesion.

05

The hydraulic pump is a pure cast iron pump

which is more wear-resistant than aluminous pump under the 3600 rpm engine high speed.

06

All hydraulic pipes adopt high-quality German imported pipes

07

Well-known crawler brand

For rubber track which uses Jin Lilong/Yuanchuang brand, a well-known crawler brand in China .

LEADING MANUFACTURING TECHNOLOGY

EXCAVATOR FACTORY

HIGHTOP has RGV assembly line and automatic welding robot, and has high static processing equipment to ensure the perfect bite and seamless welding of machine parts.